

Seal-Tite Flange Accessory Packs Class 125 & Class 250

UNITED

Seal-Tite Ring and Full Face



Flange Size	1/8" Full Face Seal-Tite	1/8" Ring Type Seal-Tite
2"	FBR-020-*	RBP-020-*
2-1/2"	FBR-025-*	RBP-025-*
3"	FBR-030-*	RBP-030-*
4"	FBR-040-*	RBP-040-*
5"	FBR-050-*	RBP-050-*
6"	FBR-060-*	RBP-060-*
8"	FBR-080-*	RBP-080-*
10"	FBR-100-*	RBP-100-*
12"	FBR-120-*	RBP-120-*
14"	FBR-140-*	RBP-140-*
16"	FBR-160-*	RBP-160-*
18"	FBR-180-*	RBP-180-*
20"	FBR-200-*	RBP-200-*
24"	FBR-240-*	RBP-240-*
30"	FBR-300-*	-
36"	FBR-360-*	-

Seal-Tite Gaskets - Full Face and Ring Type to fit ANSI B16.1-Class 125 Flanges.

Reference Standard: ANSI B16.1 - Flange Dimensions - Class 125

Material Standard: SBR

Heavy Hex Head Bolts and Nuts

Reference Standard: Heavy hex head steel bolts to ANSI B18.2.1 with heavy hex steel nuts to ANSI B18.2.2. Bolts to be threaded to ANSI B1.1 unified inch screw threads, Class 2A external & Class 2B internal.

Material Standard: to conform to ASTM A307 specification for carbon steel externally threaded standard fasteners, Grade B. Zinc plated - ASTM B633, Stainless Steel 304 & 316 Bolts - ASTM F593 Stainless Steel 302 & 316 Nuts - ASTM F594

*Add suffix:

“Z” for Zinc Plated.

“304” for 304 Stainless Steel

“316” for 316 Stainless Steel

“250” for Zinc Class 250 Flange Accessories



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



NAPAC - UNITED Distribution Centers

229 Southbridge Street, Worcester, MA 01608
Tel: (800) 807-2215 Fax: (800) 807-2214
www.napacinc.com

Jacksonville, Florida

1218