

# Seal-Tite Flange Accessory Packs

Class 125 & Class 250

**UNITED  
BRAND**

## Seal-Tite Ring and Full Face



Flange Size	1/8" Full Face Seal-Tite	1/8" Ring Type Seal-Tite
2"	FBR-020-*	RBP-020-*
2-1/2"	FBR-025-*	RBP-025-*
3"	FBR-030-*	RBP-030-*
4"	FBR-040-*	RBP-040-*
5"	FBR-050-*	RBP-050-*
6"	FBR-060-*	RBP-060-*
8"	FBR-080-*	RBP-080-*
10"	FBR-100-*	RBP-100-*
12"	FBR-120-*	RBP-120-*
14"	FBR-140-*	RBP-140-*
16"	FBR-160-*	RBP-160-*
18"	FBR-180-*	RBP-180-*
20"	FBR-200-*	RBP-200-*
24"	FBR-240-*	RBP-240-*
30"	FBR-300-*	-
36"	FBR-360-*	-

**Seal-Tite Gaskets - Full Face and Ring Type to fit ANSI B16.1-Class 125 Flanges.**

**Reference Standard:** ANSI B16.1 - Flange Dimensions - Class 125

**Material Standard:** SBR

**Heavy Hex Head Bolts and Nuts**

**Reference Standard:** Heavy hex head steel bolts to ANSI B18.2.1 with heavy hex steel nuts to ANSI B18.2.2. Bolts to be threaded to ANSI B1.1 unified inch screw threads, Class 2A external & Class 2B internal.

**Material Standard:** to conform to ASTM A307 specification for carbon steel externally threaded standard fasteners, Grade B. Zinc plated - ASTM B633, Stainless Steel 304 & 316 Bolts - ASTM F593 Stainless Steel 302 & 316 Nuts - ASTM F594

\*Add suffix:

"Z" for Zinc Plated.

"304" for 304 Stainless Steel

"316" for 316 Stainless Steel

"250" for Zinc Class 250 Flange Accessories



**NAPAC, Inc.**

229 Southbridge Street, Worcester, MA 01608 U.S.A.

Tel: (800) 807-2215 • Fax: (800) 807-2214 • [www.napacinc.com](http://www.napacinc.com)

0113