

## UL/FM GATE VALVES cont...

### Series 2510 (NRS) & Series 2530 (OS&Y) Gate Valve

ANSI B16.1/Class 250 Bolt Pattern - Ductile Iron Body - Resilient Seated - **UL/FM** - **NSF 61 FBE** less Accessories

Series 2510 NRS - Flanged Ends			
Size	Part No.	Weight	List Price
2	2510FF-120	31	P.O.A
2-1/2	2510FF-125	36	P.O.A
3	2510FF-130	47	P.O.A
4	2510FF-140	59	\$1,292.00
5	2510FF-150	102	\$2,044.00
6	2510FF-160	102	\$2,698.00
8	2510FF-180	163	\$5,880.00
10	2510FF-200	262	\$7,008.00
12	2510FF-220	367	P.O.A
14	2510FF-240	560	P.O.A
16	2510FF-260	604	P.O.A
18	2510FF-280	2100	P.O.A
20	2510FF-300	2280	P.O.A
24	2510FF-340	3230	P.O.A

Series 2530 - OS&Y - Flanged Ends			
Size	Part No.	Weight	List Price
2	2530FF-120	39	\$1,055.00
2-1/2	2530FF-125	44	\$1,055.00
3	2530FF-130	55	\$1,075.00
4	2530FF-140	66	\$1,305.00
5	2530FF-150	100	\$2,260.00
6	2530FF-160	100	\$2,065.00
8	2530FF-180	110	\$2,765.00
10	2530FF-200	170	\$6,300.00
12	2530FF-220	265	\$7,554.00
14	2530FF-240	375	P.O.A
16	2530FF-260	713	P.O.A
18	2530FF-280	2100	P.O.A
20	2530FF-300	2280	P.O.A
24	2530FF-340	3230	P.O.A

NOTE: Shaded areas currently non-stock (8-12 week lead times ARO). Please call for availability.  
 \*Use suffix "L" for open left or "R" for open right  
 (i.e. 2510FF-160L)

## UL/FM POST INDICATORS

### Series 5400 & 5450 - VERTICAL GROUND POST INDICATOR

### Series 5500 - WALL POST INDICATOR

Ground Post Indicators - Adjustable Bury Length			
Valve Size	Part No.	Weight	List Price
4"-12"	5400GP (2 - 8' bury)*	238	\$1,252.00
14"-24"	5450GP	550	\$4,667.00

Wall Post Indicators			
Valve Size	Part No.	Weight	List Price
4"-12"	5500WP	110	\$885.00

Ground Post Extension Kits			
Extension Length	Part No.	Weight	List Price
6"	5400E-06	15	\$340.00
12"	5400E-12	20	\$357.00
18"	5400E-18	25	\$376.00
24"	5400E-24	30	\$397.00
30"	5400E-30	35	\$424.00
36"	5400E-36	40	\$451.00
42" & up	5400E-xx		P.O.A

Supervisory Switch (for Indicator Posts)		
Size	Part No.	List Price
All Sizes	PCVS-2	\$305.00

NOTE: Shaded areas currently non-stock. Please call for availability.  
 \*Use suffix "R" for Open Right (i.e. 5400GP-R)