

# UNI-FIT<sup>®</sup>

## SERIES 6130

**Joint Restraint for  
PVC Pipe/MJ Fittings**

For restraining PVC Pipe to  
Mechanical Joint or Push-On  
Fittings

- 360° Full contact and support of the pipe wall - will not damage or distort pipe.
- Restraint devices produced of high strength ductile iron, machined on CNC equipment to exacting tolerances.
- “Pad To Pad” Feature - Visual indicator of correct installation.
- Can be installed on new or existing pipe installations.
- Rated at full rated pressure of PVC pipe, min. 2:1 safety factor.



Nominal Pipe Size	AWWA C-900/C-905 PVC PIPE		Restraint Rods/Nuts		Clamp Bolts		Approx. Weight/lbs.
	O.D.	Part No.	No.	Size	No.	Size	
4"	4.80	6130-04-C	2	3/4" x 7"	2	5/8" x 4"	8
6"	6.90	6130-06-C	2	3/4" x 7"	2	5/8" x 4"	10
8"	9.05	6130-08-C	2	3/4" x 7"	2	3/4" x 4"	15
10"	11.10	6130-10-C	4	3/4" x 7"	2	7/8" x 5"	25
12"	13.20	6130-12-C	4	3/4" x 7"	2	7/8" x 5"	27
14"	15.30	6130-14-C	6	3/4" x 17"	4	7/8" x 7"	55
16"	17.40	6130-16-C	6	3/4" x 17"	4	7/8" x 7"	60
18"	19.50	6130-18-C	8	3/4" x 17"	4	1" x 7"	75
20"	21.60	6130-20-C	8	3/4" x 24"	6	1-1/8" x 10"	115
24"	25.80	6130-24-C	12	3/4" x 24"	6	1-1/8" x 10"	145
30"	32.00	6130-30-C	14	1" x 24"	8	1-1/8" x 10"	330
36"	38.30	6130-36-C	14	1" x 24"	8	1-1/8" x 10"	354

Design and dimensions subject to change without notice.



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**NAPAC - UNITED Distribution Centers**

229 Southbridge Street, Worcester, MA 01608  
Tel: (800) 807-2215 Fax: (800) 807-2214  
[www.napacinc.com](http://www.napacinc.com)

Jacksonville, Florida

# UNI-FIT<sup>®</sup>

## SERIES 6190

For restraining PVC Pipe Bells  
(Bell and Spigot Joints)

Fast & Economical Restraint of PVC Pipe Bell & Spigot Joints.

Restraint Rings provide 360° full contact and support of pipe wall.

Restraint Rings connected by high strength, low alloy rods/nuts.

For use on **NEW OR EXISTING** PVC Pipe Bells.

Rated at full rated pressure of pipe, 2:1 safety factor.

**“Recommended Restrained Lengths of PVC Pipe”** calculated at no charge.

Contact factory for details.

Joint Restraint  
for PVC Pipe Bells

Sizes 4" ~ 12"



Sizes 14" ~ 24"



Sizes 30" & 36"



Nominal Pipe Size	AWWA C-900/C-905 PVC PIPE		Restraint Rods/Nuts		Clamp Bolts		Approx. Weight/lbs.
	O.D.	Part No.	No.	Size	No.	Size	
4"	4.80	6190-04-C	2	3/4" x 17"	4	5/8" x 4"	17
6"	6.90	6190-06-C	2	3/4" x 17"	4	5/8" x 4"	19
8"	9.05	6190-08-C	2	3/4" x 17"	4	3/4" x 4"	29
10"	11.10	6190-10-C	4	3/4" x 24"	4	7/8" x 5"	53
12"	13.20	6190-12-C	4	3/4" x 24"	4	7/8" x 5"	57
14"	15.30	6190-14-C	6	3/4" x 30"	8	7/8" x 7"	136
16"	17.40	6190-16-C	6	3/4" x 30"	8	7/8" x 7"	147
18"	19.50	6190-18-C	8	3/4" x 30"	8	1" x 7"	206
20"	21.60	6190-20-C	8	3/4" x 36"	8	1-1/8" x 10"	263
24"	25.80	6190-24-C	12	3/4" x 36"	8	1-1/8" x 10"	406
30"	32.00	6190-30-C	14	1" x 40"	16	1-1/8" x 10"	601
36"	38.30	6190-36-C	14	1" x 40"	16	1-1/8" x 10"	672



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**NAPAC - UNITED Distribution Centers**

229 Southbridge Street, Worcester, MA 01608  
Tel: (800) 807-2215 Fax: (800) 807-2214  
[www.napacinc.com](http://www.napacinc.com)

1218

Jacksonville, Florida